

### **Industrial & Commercial LED Lighting Company**

4403 Greenbriar Dr, Stafford, Texas 77477 Tel No. 1-800-8385070 Monday - Friday 8:30 AM to 5:30 PM

# 805X SERIES CCT & WATTAGE SELECTABLE **LED VAPOR TIGHT**





**(---W---)** WATTAGE SELECTABLE

CCT SELECTABLE



CCT












#### Introduction:





- Available in two sizes, this LED Vapor Tight Fixture offers selectable wattage and color temperature, making it easy for distributors to stock and increase flexibility for project changes.
- It can be surface mounted to the ceiling or wall, or suspended depending on the application. Sensor and emergency battery backup are optional.

#### **Product Features:**

# **Construction:**

• Rugged and durable construction with plastic housing.

#### **Electrical:**

- 0 10v dimmable driver, which can dim from 100% down to off.
- The Input voltage is AC120-277V/120-347V.

### **Optics:**

- LED chips support CCT selectable with CRI>80
- Sealed optic available in 120° beam angle.


#### **Mounting:**

• Support optional surface or pendant mounting.

• Housing is permanent pearl gray color.

## Accessories







**Emergency backup** 



Suspended mounting kit

# **Electrical Data**

Voltage (V)	Model Series		
	X-VTL(50/40/30)W	X-VTL(80/70/60)W	
	Current (A)	Current (A)	
120V	0.42	0.67	
208V	0.24	0.38	
240V	0.21	0.33	
277V	0.18	0.29	
347V	0.14	0.23	

# **Ordering Guide**

- 805X2 50W for selectable wattage 30/40/50W
- 805X2 80W for selectable wattage 60/70/80W

PRODUCT TYPE	PRODUCT NAME	CCT SELECTABLE	INPUT VOLTAGE	WATTAGE SELECTABLE	LUMENS	SIZE
VAPOR TIGHT	805X	X= 30/40/50K	2 = 120-277V	30/40/50W	Max 6500lm	4FT
LIGHT	8037	X= 30/40/30K	Z = 120-277V	30/40/30	IVIAX 0300IIII	411
VAPOR TIGHT	805X	X= 30/40/50K	2 = 120-277V	60/70/80W	Max 10400lm	8FT
LIGHT	803X	X= 30/40/30K	Z = 120-277V	00/70/80	IVIAX 10400IIII	ori